

BAR STOOL

TECHNICAL SPECIFICATION

DESCRIPTION

Backless upholstered bar stool. "Bulldog" style by Southwest Contract or similar.

FINISH

Upholstered seat using Type 1 fabric and providing multiple grades to choose from, light oak wood finish and steel scuff guards attached to all four foot rests on the leg braces.

MEASUREMENTS

15.5" W x 15.5" D x 30" H

CORE MATERIAL

- ◇ All parts are constructed from select beech hardwood.
- ◇ Wood species: Beech hardwood. No clear cutting or rain forest materials allowed.
- ◇ All lumber shall be thoroughly air seasoned before kiln drying to a moisture content of 6 percent or less. The lumber is then allowed to temper before milling. All parts selected from steam bending are partially air seasoned before bending, the kiln dried moisture content is less than 6 percent after bending.

FABRICATION

- ◇ All components shall be mortise and tenon joints.
- ◇ Legs are made from 2" lumber, tapered from the seat rail to the floor.
- ◇ Solid wood seat is made from 1" lumber.
- ◇ High solids glue and reinforced with wood blocks.
- ◇ Sanding of bare wood of the assembled stool is thoroughly sanded using 120 grit paper.
- ◇ Catalyzed sealer will be sprayed onto all wood parts completely sealing wood including the underside of seat. Once dry the sealer is sanded using 320 grit sand paper, before a final sanding to remove any sanding marks using Scotch Brite pads. A final durable catalyzed lacquer is used. This lacquer is very durable and will withstand a commercial environment.
- ◇ Steel scuff guards will be attached to all four leg braces.
- ◇ A final inspection shall be performed prior to packaging to ensure a high level of quality control.